

LINKING USER-DEFINED PANELS TO EXISTING PRODUCT PANELS**BACKGROUND OF THE INVENTION****1. Technical Field:**

5 The present invention relates generally to an improved data processing system and in particular to a method and apparatus for processing user input. Still more particularly, the present invention provides a method, apparatus, and computer implemented instructions for linking or associating panels or windows in a graphical user interface.

2. Description of Related Art:

15 In data processing systems, graphical user interfaces (GUIs) are an important part of the input/output interface employed by users to interact with data processing systems. A GUI is used to present data to a user in various forms. The data may be presented using text, graphics, or even video. Additionally, GUIs often provide controls, such as buttons, sliders, or scroll bars, used to navigate within the data processing system.

20 Applications provided to users include GUIs, which provide access to the functionality of the applications. Some existing application products, however, do not necessarily provide functions needed by a user. Some applications allow for the adding of predefined functions to a GUI. For example, the user may add a function, such as save all open files, to a word processing program by selecting a tool bar function provided with the word processing program. This feature allows a user to add

Docket No. AUS920010617US1

functions, but only those predefined in the application. In some cases, a user may desire to add a function that is not predefined by the application. Currently, such a feature is not readily available to users.

- 5 Therefore, it would be advantageous to have an improved method, apparatus, and computer implemented instructions for adding functionality to a graphical user interface.

09918810-073101
T07E20-0788T660

SUMMARY OF THE INVENTION

The present invention provides a method, apparatus, and computer implemented instructions for linking panels to an existing panel in a graphical user interface in a data processing system. The panel includes a set of data objects for a panel and a set of navigation objects for the panel. The panel also includes a first list of data objects within the set of data objects, wherein the first list contains an identification of a data type for each data object within the first list. A second list of navigation objects is included in the panel in which the second list includes an event, a target object associated with the event, and a target object action associated with the target object in which the target object action is applied to the target object for each navigation object within the list.

TO: 09-07-2000

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself, however, as well as a preferred mode of use, further objectives and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

Figure 1 is a pictorial representation of a data processing system in which the present invention may be implemented in accordance with a preferred embodiment of the present invention;

Figure 2 is a block diagram of a data processing system in which the present invention may be implemented;

Figure 3 is a diagram of a set of panels in accordance with a preferred embodiment of the present invention;

Figure 4 is a diagram of a panel system in accordance with a preferred embodiment of the present invention;

Figure 5 is a diagram of a panel system in accordance with a preferred embodiment of the present invention;

Figure 6 is a diagram illustrating a set of panels in accordance with a preferred embodiment of the present invention;

Figure 7 is a table of name value pairs for identifying panels in accordance with a preferred embodiment of the present invention;

Docket No. AUS920010617US1

Figure 8 is a diagram of pseudo code for a panel in accordance with a preferred embodiment of the present invention;

Figure 9 is a flowchart of a process used for
5 obtaining panel data in accordance with a preferred embodiment of the present invention; and

Figure 10 is a diagram of pseudo code for obtaining panel data for a current panel in accordance with a preferred embodiment of the present invention.

094810-038T660

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference now to the figures and in particular with reference to **Figure 1**, a pictorial representation of a data processing system in which the present invention may be implemented is depicted in accordance with a preferred embodiment of the present invention. A computer **100** is depicted which includes system unit **102**, video display terminal **104**, keyboard **106**, storage devices **108**, which may include floppy drives and other types of permanent and removable storage media, and mouse **110**. Additional input devices may be included with personal computer **100**, such as, for example, a joystick, touchpad, touch screen, trackball, microphone, and the like. Computer **100** can be implemented using any suitable computer, such as an IBM RS/6000 computer or IntelliStation computer, which are products of International Business Machines Corporation, located in Armonk, New York. Although the depicted representation shows a computer, other embodiments of the present invention may be implemented in other types of data processing systems, such as a network computer. Computer **100** also preferably includes a graphical user interface (GUI) that may be implemented by means of systems software residing in computer readable media in operation within computer **100**.

With reference now to **Figure 2**, a block diagram of a data processing system is shown in which the present invention may be implemented. Data processing system **200** is an example of a computer, such as computer **100** in **Figure 1**, in which code or instructions implementing the

Docket No. AUS920010617US1

processes of the present invention may be located. Data processing system **200** employs a peripheral component interconnect (PCI) local bus architecture. Although the depicted example employs a PCI bus, other bus architectures such as Accelerated Graphics Port (AGP) and Industry Standard Architecture (ISA) may be used. Processor **202** and main memory **204** are connected to PCI local bus **206** through PCI bridge **208**. PCI bridge **208** also may include an integrated memory controller and cache memory for processor **202**. Additional connections to PCI local bus **206** may be made through direct component interconnection or through add-in boards. In the depicted example, local area network (LAN) adapter **210**, small computer system interface (SCSI) host bus adapter **212**, and expansion bus interface **214** are connected to PCI local bus **206** by direct component connection. In contrast, audio adapter **216**, graphics adapter **218**, and audio/video adapter **219** are connected to PCI local bus **206** by add-in boards inserted into expansion slots. Expansion bus interface **214** provides a connection for a keyboard and mouse adapter **220**, modem **222**, and additional memory **224**. SCSI host bus adapter **212** provides a connection for hard disk drive **226**, tape drive **228**, and CD-ROM drive **230**. Typical PCI local bus implementations will support three or four PCI expansion slots or add-in connectors.

An operating system runs on processor **202** and is used to coordinate and provide control of various components within data processing system **200** in **Figure 2**. The operating system may be a commercially available operating system such as Windows 2000, which is available from Microsoft Corporation. An object oriented programming

system such as Java may run in conjunction with the operating system and provides calls to the operating system from Java programs or applications executing on data processing system **200**. "Java" is a trademark of Sun Microsystems, Inc. Instructions for the operating system, the object-oriented programming system, and applications or programs are located on storage devices, such as hard disk drive **226**, and may be loaded into main memory **204** for execution by processor **202**.

Those of ordinary skill in the art will appreciate that the hardware in **Figure 2** may vary depending on the implementation. Other internal hardware or peripheral devices, such as flash ROM (or equivalent nonvolatile memory) or optical disk drives and the like, may be used in addition to or in place of the hardware depicted in **Figure 2**. Also, the processes of the present invention may be applied to a multiprocessor data processing system.

For example, data processing system **200**, if optionally configured as a network computer, may not include SCSI host bus adapter **212**, hard disk drive **226**, tape drive **228**, and CD-ROM **230**. In that case, the computer, to be properly called a client computer, must include some type of network communication interface, such as LAN adapter **210**, modem **222**, or the like. As another example, data processing system **200** may be a stand-alone system configured to be bootable without relying on some type of network communication interface, whether or not data processing system **200** comprises some type of network communication interface. As a further example, data processing system **200** may be a personal digital assistant (PDA), which is configured with ROM

Docket No. AUS920010617US1

and/or flash ROM to provide nonvolatile memory for storing operating system files and/or user-generated data.

The depicted example in **Figure 2** and above-described examples are not meant to imply architectural limitations. For example, data processing system **200** also may be a notebook computer or hand held computer in addition to taking the form of a PDA. Data processing system **200** also may be a kiosk or a Web appliance.

The processes of the present invention are performed by processor **202** using computer implemented instructions, which may be located in a memory such as, for example, main memory **204**, memory **224**, or in one or more peripheral devices **226-230**.

The present invention provides an improved method, apparatus, and computer implemented instructions for linking panels in a graphical user interface (GUI). The mechanism of the present invention allows new panels to be linked to existing panels in which the existing panels do not need to be modified or know what processing occurs in the new panels.

Turning next to **Figure 3**, a diagram of a set of panels is depicted in accordance with a preferred embodiment of the present invention. Panel system **300** includes product panel **302**, custom panel **304**, custom panel **306**, custom panel **308**, custom panel **310**, and custom panel **312**. In this example, product panel **302** does not care about the data located in custom panels **304-312**. These custom panels are extensions of the product in panel system **300**. Only the custom panels know what data the user has defined on those custom panels. To achieve

Docket No. AUS920010617US1

5 this situation, a product panel may link to another product panel or a custom panel. A custom panel can only link to another custom panel not any product panel. In this example, product panel **302** is linked to custom panel **304** and custom panel **308**. Custom panel **304** has a link to custom panel **306**, while custom panel **308** is linked to custom panel **310** and custom panel **312**. None of the links for custom panels lead to product panel **302**.

10 Turning next to **Figure 4**, a diagram of a panel system is depicted in accordance with a preferred embodiment of the present invention. Panel system **400** includes product panel **402**, product panel **404**, custom panel **406**, and custom panel **408**. In this example, product panel **404** needs to know the data in custom panel **406**. Product panel **402** is linked to custom panel **406** and product panel **404**. Custom panel **406** has a link to custom panel **408** and product panel **404**, and product panel **404** has a link to custom panel **408**. In this case, a product panel can link to either another product panel or a custom panel. A custom panel can also link to either a product panel or a custom panel. The custom panels are truly integrated with the product.

20 With reference next to **Figure 5**, a diagram of a panel system is depicted in accordance with a preferred embodiment of the present invention. Panel system **500** includes product panel **502**, custom panel **504**, and custom panel **506**. Panel system **500** also requires that the product panels know what data is present in custom panels. Panel subsystem **500** is an example of circular linkage between panels.

Turning next to **Figure 6**, a diagram illustrating a set of panels is depicted in accordance with a preferred embodiment of the present invention. In this example, panel system **600** include product panel **602**, custom panel **604**, custom panel **606**, custom panel **608**, and custom panel **610**. Product panel **602** includes information field **612** and information field **614** as well as text field **616** and text field **618**. Additionally, product panel **602** includes "OK" button **620**, "Cancel" button **622**, "Link1" button **624**, "X" button **626**, and "Link2" button **628**. "Link1" button **624** provides a link to custom panel **604**, while "Link2" button **628** provides a link to custom panel **606**.

Custom panel **604** includes information field **630** and text field **632**. Custom panel **604** also includes "OK" button **634**, "Cancel" button **636**, "Link1" button **638**, and "Link2" button **640**. "Link1" button **638** provides a link to custom panel **608**, while "Link2" button **640** provides a link to custom panel **610**. Custom panel **606** includes information field **642** and text field **644** as well as "OK" button **646** and "Cancel" button **648**.

Custom panel **608** includes information field **650**, text **652**, "OK" button **654**, and "Cancel" button **656**. In a similar fashion, custom panel **610** includes information field **658**, text field **660**, "OK" button **662**, and "Cancel" button **664**.

In these examples, buttons, such as an "OK" button, "Apply" button, "Cancel" button, and a "Help" button are non-navigation buttons. Other buttons associated with a target panel are link buttons, such as "Link1" button **624** in product panel **602** or "Link1" button **638** in custom panel **604**.

Alternatively, a button may simply perform a task, which does not bring up an additional panel. For example, a button may only play a voice message to the user. This kind of button does not participate in any navigation and can be ignored here. "X" button **626** in product panel **602** falls into this category. This kind of button is called a "non-link" button.

In this example, a property is a set of name-value pairs that can be stored into the database table. An example is below:

```
{userId=John, password-abclxyz}
```

where 2 name-value pairs exist in the property, the name "userId" with value "John" and name "password" with the value "abclxyz". "UserId" corresponds to information field **612**, while "John" corresponds to data in text field **616** in product panel **602**. Next, "password" corresponds to information field **614**, while "abclxyz" corresponds to the data in text field **618** in product panel **602**.

In order to integrate product panel **602** and custom panels **604-610**, product panel **602** needs to know about all the data on these custom panels. First, product panel **602** needs to know how many custom panels are linked into the product. Next, product panel **602** needs to know in what order the custom panels are linked. Product panel **602** also needs to know what data is contained on each of the custom panels.

In this example, product panel **602** has two link buttons, "Link1" button **624** and "Link2" button **628**. Additionally, product panel **602** has one non-link button, "X" button **626**. Custom panel **604** has two link buttons, "Link1" button **638** and "Link2" button **640**. Custom panels

2025-07-10 09:10:00

Docket No. AUS920010617US1

606, **608**, and **610** are also called leaf panels, which have no link buttons.

With reference now to **Figure 7**, a table of name value pairs for identifying panels is depicted in accordance with a preferred embodiment of the present invention. Table **700** includes the information needed for identifying information about custom panels for panel system **600** in **Figure 6**. In this example, entry **702** is associated with custom panel **604**, entry **704** is associated with custom panel **608**, entry **706** is associated with custom panel **610**, and entry **708** is associated with custom panel **606** in panel system **600**. In each entry, a panel identification and a data field are present. Each data field contains a data property and a navigation buttons property.

In the example in table **700**, the data property in each entry contains a set of name-value pairs in which the name is the data class type and the value is the object name.

The navigation buttons property contains a set of name-value pairs in which the name is the link button, and the value is the target panel. This information can be provided by a programmer who creates the custom panels. This information may be stored and retrieved from a file. Alternatively, if the panels are written using Java, this information also may be retrieved directly from the custom panel Java file.

Turning next to **Figure 8**, a diagram of pseudo code for a panel is depicted in accordance with a preferred embodiment of the present invention. Code **800** is an example of Java code, which may be used for a custom panel, such as custom panel **604** in **Figure 6**.

Docket No. AUS920010617US1

By scanning through the CP1.java file, both:

data property: {JtextField=Text1}

navigation buttons property: {Link1=CP2, Link2=CP3}

can be obtained. This information is the information

5 associated with entry **702** in **Figure 7**. Next, the data of JtextField=Text1 can be obtained by applying:

Text1.getText();

which returns the String "abc".

10 On product panel **602** in **Figure 6**, if "OK" button **620** is pressed, product panel **602** will be closed and all the data buttons on product panel **602** and also all the data on the linked custom panels, such as custom panel **604** and custom panel **606** in **Figure 6**, will be stored into a database.

15 On product panel **602**, if "Cancel" button **622** is pressed product panel **602** will be closed. All the changed data or settings on this product panel and all the linked custom panels will be discarded. The original data on those panels will be displayed next time when the
20 panels are shown.

If the user enters "abc" in custom panel **604** in **Figure 6** and then selects "OK" button **634**, custom panel **604** will be closed. If the user enters userId "John" into text field **616**, enters the password "abc1xyz" in text
25 field **618**, and then presses "OK" button **620** on product panel **602**, the property:

{UserId=John, Password=abc1xyz, Text1=abc}

will be stored into a database.

30 Since the user defined names on the custom panels, such as Text1 in information field **630** may be duplicated on another panel, such as product panel **602**, confusion

2025-10-07 10:00:00

Docket No. AUS920010617US1

may occur in identifying different objects. As a result, in these examples, all of the names on the custom panels are assigned using a unique name. In order to accomplish this type of assignment, a special header "C_" is added

5 to the custom defined name as:

{UserId=John, Password=abc1xyz, C_Text1=abc}

During display, the extra header "C_" is removed.

When the name is stored, the extra header "C_" is added in front of the custom defined name.

10 In these examples, "product linking panel" is defined as a product panel that contains the custom link buttons.

With reference now to **Figure 9**, a flowchart of a process used for obtaining panel data is depicted in
15 accordance with a preferred embodiment of the present invention. The process illustrated in **Figure 9** may be implemented in a data processing system, such as data processing system **200** in **Figure 2**. This process may be implemented as a recursive process.

20 The process begins with a determination as to whether a current panel is a custom panel (step **900**). If the current panel is a custom panel, "C_" is attached in front of the data name, and the CURRENT_PANEL data is put into the property (step **902**). In step **902**, the data is
25 data associated with a panel from user input. For example, custom panel **904** in **Figure 9** has only one set of data. As a result, the process would not return to step **902**. If another data field were present, then the process would return to step **902**. The "C_" is used to
30 differentiate the data name in a custom panel to avoid possibly using the same data name as in a product panel. In these examples, CURRENT_PANEL is the product linking

Docket No. AUS920010617US1

panel. This property is similar to the data property and navigations button property illustrated in **Figure 10**.

Next, a determination is made as to whether all of the data on the CURRENT_PANEL has been put into the property (step **904**). If the answer to this determination is yes, a BUTTON_LIST is retrieved for the CURRENT_PANEL (step **906**). The CURRENT_BUTTON is set equal to the next button on the BUTTON_LIST (step **908**). BUTTON_LIST may be defined by a programmer or may be obtained from parsing the existing Java code for the panel, such as in **Figure 8**.

A determination is then made as to whether the CURRENT_BUTTON is not an "OK" button, not an "Apply" button, not a "Cancel" button, not a "Help" button, and has a TARGET_PANEL (step **910**). If the CURRENT_BUTTON is not an "OK" button, not an "Apply" button, not a "Cancel" button, not an "Help" button and has a TARGET_PANEL, the TARGET_PANEL is set equal to the target panel of the CURRENT_BUTTON and a call GET_CUSTOM_PANEL_DATA (CURRENT_PANEL) is made (step **912**). Next, a determination is made as to whether all of the buttons on the CURRENT_PANEL have been examined (step **914**). If all of the buttons on the CURRENT_PANEL have been examined, the process terminates. Otherwise, the process returns to step **912** as described above.

Turning back to step **910**, if the CURRENT_BUTTON is an "OK" button, or "Apply" button, or "Cancel" button, or "Help" button, or does not have a TARGET_PANEL, the process proceeds to step **914** as described above. With reference again to step **904**, if all of the data on the CURRENT_PANEL has not been put into the property, the

Docket No. AUS920010617US1

process returns to step **902**. Turning again to step **900**, if the current panel is not a custom panel, the process proceeds to step **906** as described above.

In applying the process in **Figure 9** to the example depicted in **Figure 6**, if product panel **602** has no custom panels attached to it and "OK" button **620** is pressed, the following property is stored into a database:

```
{UserId=John, Password=abc1xyz}
```

In this example, since custom panel **604** is attached to product panel **602** through "Link1" button **624**, the following property is added as:

```
{UserId=John, Password=abc1xyz, C_Text1=abc}
```

In this example, since custom panel **608** is attached to custom panel **604** through "Link1" button **638**, the following property is added as:

```
{UserId=John, Password=abc1xyz, C_Text1=abc, C_Text2=def}
```

Custom panel **610** is attached to custom panel **604** through "Link2" button **640**, the following property is added as:

```
{UserId=John, Password=abc1xyz, C_Text1=abc, C_Text2=def,  
C_Text3=ghi}
```

As shown in **Figure 6**, custom panel **606** is attached to product panel **602** through "Link2" button **628**, the

Docket No. AUS920010617US1

following property is added as:

{UserId=John, Password=abc1xyz, C_Text1=abc, C_Text2=def, C_Text3=ghi, C_Text4=xyz}.

Turning next to **Figure 10**, a diagram of pseudo code
5 is provided for obtaining panel data for a current panel
in accordance with a preferred embodiment of the present
invention. In this example, pseudo code **1000** may be
implemented in a data processing system, such as data
processing system **200** in **Figure 2**. This pseudo code is
10 an example of code that may be created to implement the
process illustrated in **Figure 9**.

Thus, the present invention provides an improved
method, apparatus, and computer implemented instructions
for adding panels to a graphical user interface. The
15 mechanism of the present invention allows for an
integration of new panels within existing panels. The
existing panels do not need to know of the processing
occurring within the new panels with this mechanism.

It is important to note that while the present
20 invention has been described in the context of a fully
functioning data processing system, those of ordinary
skill in the art will appreciate that the processes of
the present invention are capable of being distributed in
the form of a computer readable medium of instructions
25 and a variety of forms and that the present invention
applies equally regardless of the particular type of
signal bearing media actually used to carry out the
distribution. Examples of computer readable media
include recordable-type media, such as a floppy disk, a
30 hard disk drive, a RAM, CD-ROMs, DVD-ROMs, and

transmission-type media, such as digital and analog communications links, wired or wireless communications links using transmission forms, such as, for example, radio frequency and light wave transmissions. The computer readable media may take the form of coded formats that are decoded for actual use in a particular data processing system.

The description of the present invention has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. The embodiment was chosen and described in order to best explain the principles of the invention, the practical application, and to enable others of ordinary skill in the art to understand the invention for various embodiments with various modifications as are suited to the particular use contemplated.